

Case No. 58072

08/29/00

8/30/00

CERTIFICATE OF MAILING BY "EXPRESS MAIL"

"EXPRESS MAIL" MAILING LABEL NUMBER E 547938553DATE OF DEPOSIT AUGUST 29, 2000ASSISTANT COMMISSIONER FOR PATENTS
WASHINGTON, DC 20231I HEREBY CERTIFY THAT THE ABOVE IS BEING DEPOSITED
WITH THE UNITED STATES PATENT AND TRADEMARK OFFICE
OFFICE TO ADJUSTABLE "MAILING LABEL" ON THE DATE
INDICATED ABOVE AND IS SUBJECT TO THE COMMISSIONER OF
PATENTS AND TRADEMARKS, WASHINGTON, D.C. 20501ERIC LINK

(TYPED OR PRINTED NAME OF PERSON MAILING PAPER OR FEE)

Eric Link
(SIGNATURE OF PERSON MAILING PAPER OR FEE)

Transmitted herewith for filing is the patent application of:

Inventor: **Kenneth E. FLICK**For: **VEHICLE SECURITY SYSTEM SHOCK SENSING SIREN AND
ASSOCIATED METHODS****Enclosed are:**

- ☒ Patent Application: 28 pages, 30 claims.
- ☒ 5 sheets of drawings.
- ☒ A declaration and power of attorney.
- ☒ A verified statement to establish small entity status under 37 CFR §§1.19 and 1.27.
- ☐ Citation Under 37 CFR 1.97 and PTO-1449.

The filing fee has been calculated as shown below:

The filing fee has been calculated as shown below.									
	(Col. 1)		(Col. 2)		SMALL ENTITY			LARGE ENTITY	
FOR:	# FILED		# EXTRA		RATE	FEE		RATE	FEE
BASIC FEE						\$ 345	OR		\$ 690
TOTAL CLAIMS	30	-20	10		X 9	\$ 90	OR	X 18	\$
INDEP CLAIMS	4	- 3	1		X 39	\$ 39	OR	X 78	\$
[] MULTIPLE DEPENDENT CLAIM PRESENTED					+	\$	OR		
* If the difference in Col. 1 is less than "0", enter "0" in Col. 2.					TOTAL	\$ 474		TOTAL	\$

- ☒ Enclosed is a check in the amount of **\$474.00** to cover:

☒ Filing Fee
Recording Assignment

- ☒ The Commissioner is authorized to charge or credit any discrepancies in fee amounts to Deposit Account No. 01-0484.

August 29, 2000
Date

Christopher F. Regan
CHRISTOPHER F. REGAN
Reg. No. 34 908
ALLEN, DYER, DOPPELT, MILBRATH & GILCHRIST, P.A.
255 South Orange Avenue - Suite 1401
P. O. Box 3791
Orlando, Florida 32802-3791
PHONE: (407) 841-2330

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Kenneth E. FLICK
Serial: Not Yet Assigned
Attorney's Docket No.: 58072
Filed: Herewith
For: **VEHICLE SECURITY SYSTEM SHOCK SENSING SIREN AND
ASSOCIATED METHODS**

**VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY
STATUS (37 CFR 1.9(f) and 1.27(b)) - INDEPENDENT INVENTOR**

As a below named inventor, I hereby declare that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees under section 41(a) and (b) of Title 35, United States Code, to the Patent and Trademark Office with regard to the invention entitled: **VEHICLE SECURITY SYSTEM SHOCK SENSING SIREN AND ASSOCIATED METHODS** described in:

- (x) the specification filed herewith
() application serial no. _____ filed _____
() patent no. _____ issued _____

I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern, or organization to which I have assigned, granted, conveyed or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

- (x) no such person, concern, or organization
() persons, concerns or organizations listed below*

*NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)

FULL NAME

ADDRESS

☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that: all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

Kenneth E. Flick
NAME OF INVENTOR

SIGNATURE OF INVENTOR

DATE

58072

1. *Chlorophyll a* (Chl *a*)
 2. *Chlorophyll b* (Chl *b*)
 3. *Chlorophyll c* (Chl *c*)
 4. *Chlorophyll d* (Chl *d*)
 5. *Chlorophyll e* (Chl *e*)
 6. *Chlorophyll f* (Chl *f*)
 7. *Chlorophyll g* (Chl *g*)
 8. *Chlorophyll h* (Chl *h*)
 9. *Chlorophyll i* (Chl *i*)
 10. *Chlorophyll j* (Chl *j*)
 11. *Chlorophyll k* (Chl *k*)
 12. *Chlorophyll l* (Chl *l*)
 13. *Chlorophyll m* (Chl *m*)
 14. *Chlorophyll n* (Chl *n*)
 15. *Chlorophyll o* (Chl *o*)
 16. *Chlorophyll p* (Chl *p*)
 17. *Chlorophyll q* (Chl *q*)
 18. *Chlorophyll r* (Chl *r*)
 19. *Chlorophyll s* (Chl *s*)
 20. *Chlorophyll t* (Chl *t*)
 21. *Chlorophyll u* (Chl *u*)
 22. *Chlorophyll v* (Chl *v*)
 23. *Chlorophyll w* (Chl *w*)
 24. *Chlorophyll x* (Chl *x*)
 25. *Chlorophyll y* (Chl *y*)
 26. *Chlorophyll z* (Chl *z*)
 27. *Chlorophyll aa* (Chl *aa*)
 28. *Chlorophyll ab* (Chl *ab*)
 29. *Chlorophyll ac* (Chl *ac*)
 30. *Chlorophyll ad* (Chl *ad*)
 31. *Chlorophyll ae* (Chl *ae*)
 32. *Chlorophyll af* (Chl *af*)
 33. *Chlorophyll ag* (Chl *ag*)
 34. *Chlorophyll ah* (Chl *ah*)
 35. *Chlorophyll ai* (Chl *ai*)
 36. *Chlorophyll aj* (Chl *aj*)
 37. *Chlorophyll ak* (Chl *ak*)
 38. *Chlorophyll al* (Chl *al*)
 39. *Chlorophyll am* (Chl *am*)
 40. *Chlorophyll an* (Chl *an*)
 41. *Chlorophyll ao* (Chl *ao*)
 42. *Chlorophyll ap* (Chl *ap*)
 43. *Chlorophyll aq* (Chl *aq*)
 44. *Chlorophyll ar* (Chl *ar*)
 45. *Chlorophyll as* (Chl *as*)
 46. *Chlorophyll at* (Chl *at*)
 47. *Chlorophyll au* (Chl *au*)
 48. *Chlorophyll av* (Chl *av*)
 49. *Chlorophyll aw* (Chl *aw*)
 50. *Chlorophyll ax* (Chl *ax*)
 51. *Chlorophyll ay* (Chl *ay*)
 52. *Chlorophyll az* (Chl *az*)
 53. *Chlorophyll aza* (Chl *aza*)
 54. *Chlorophyll abz* (Chl *abz*)
 55. *Chlorophyll acz* (Chl *acz*)
 56. *Chlorophyll adz* (Chl *adz*)
 57. *Chlorophyll aez* (Chl *aez*)
 58. *Chlorophyll afz* (Chl *afz*)
 59. *Chlorophyll agz* (Chl *agz*)
 60. *Chlorophyll ahz* (Chl *ahz*)
 61. *Chlorophyll aiz* (Chl *aiz*)
 62. *Chlorophyll ajz* (Chl *ajz*)
 63. *Chlorophyll akz* (Chl *akz*)
 64. *Chlorophyll alz* (Chl *alz*)
 65. *Chlorophyll amz* (Chl *amz*)
 66. *Chlorophyll anz* (Chl *anz*)
 67. *Chlorophyll aoz* (Chl *aoz*)
 68. *Chlorophyll apz* (Chl *apz*)
 69. *Chlorophyll aqz* (Chl *aqz*)
 70. *Chlorophyll arz* (Chl *arz*)
 71. *Chlorophyll asz* (Chl *asz*)
 72. *Chlorophyll atz* (Chl *atz*)
 73. *Chlorophyll auz* (Chl *auz*)
 74. *Chlorophyll avz* (Chl *avz*)
 75. *Chlorophyll awz* (Chl *awz*)
 76. *Chlorophyll axz* (Chl *axz*)
 77. *Chlorophyll ayz* (Chl *ayz*)
 78. *Chlorophyll ayz* (Chl *ayz*)
 79. *Chlorophyll azz* (Chl *azz*)
 80. *Chlorophyll azaa* (Chl *aza*)
 81. *Chlorophyll abz* (Chl *abz*)
 82. *Chlorophyll acz* (Chl *acz*)
 83. *Chlorophyll adz* (Chl *adz*)
 84. *Chlorophyll aez* (Chl *aez*)
 85. *Chlorophyll afz* (Chl *afz*)
 86. *Chlorophyll agz* (Chl *agz*)
 87. *Chlorophyll ahz* (Chl *ahz*)
 88. *Chlorophyll aiz* (Chl *aiz*)
 89. *Chlorophyll ajz* (Chl *ajz*)
 90. *Chlorophyll akz* (Chl *akz*)
 91. *Chlorophyll alz* (Chl *alz*)
 92. *Chlorophyll amz* (Chl *amz*)
 93. *Chlorophyll anz* (Chl *anz*)
 94. *Chlorophyll aoz* (Chl *aoz*)
 95. *Chlorophyll apz* (Chl *apz*)
 96. *Chlorophyll aqz* (Chl *aqz*)
 97. *Chlorophyll arz* (Chl *arz*)
 98. *Chlorophyll asz* (Chl *asz*)
 99. *Chlorophyll atz* (Chl *atz*)
 100. *Chlorophyll auz* (Chl *auz*)
 101. *Chlorophyll avz* (Chl *avz*)
 102. *Chlorophyll awz* (Chl *awz*)
 103. *Chlorophyll axz* (Chl *axz*)
 104. *Chlorophyll ayz* (Chl *ayz*)
 105. *Chlorophyll ayz* (Chl *ayz*)
 106. *Chlorophyll azz* (Chl *azz*)
 107. *Chlorophyll azaa* (Chl *aza*)
 108. *Chlorophyll abz* (Chl *abz*)
 109. *Chlorophyll acz* (Chl *acz*)
 110. *Chlorophyll adz* (Chl *adz*)
 111. *Chlorophyll aez* (Chl *aez*)
 112. *Chlorophyll afz* (Chl *afz*)
 113. *Chlorophyll agz* (Chl *agz*)
 114. *Chlorophyll ahz* (Chl *ahz*)
 115. *Chlorophyll aiz* (Chl *aiz*)
 116. *Chlorophyll ajz* (Chl *ajz*)
 117. *Chlorophyll akz* (Chl *akz*)
 118. *Chlorophyll alz* (Chl *alz*)
 119. *Chlorophyll amz* (Chl *amz*)
 120. *Chlorophyll anz* (Chl *anz*)
 121. *Chlorophyll aoz* (Chl *aoz*)
 122. *Chlorophyll apz* (Chl *apz*)
 123. *Chlorophyll aqz* (Chl *aqz*)
 124. *Chlorophyll arz* (Chl *arz*)
 125. *Chlorophyll asz* (Chl *asz*)
 126. *Chlorophyll atz* (Chl *atz*)
 127. *Chlorophyll auz* (Chl *auz*)
 128. *Chlorophyll avz* (Chl *avz*)
 129. *Chlorophyll awz* (Chl *awz*)
 130. *Chlorophyll axz* (Chl *axz*)
 131. *Chlorophyll ayz* (Chl *ayz*)
 132. *Chlorophyll ayz* (Chl *ayz*)
 133.

VEHICLE SECURITY SYSTEM SHOCK SENSING
SIREN AND ASSOCIATED METHODS

Field of the Invention

The present invention relates to the field of security systems, and, more particularly, to a vehicle security system including a siren also sensing shocks
5 and associated methods.

Background of the Invention

Vehicle security systems are widely used to deter vehicle theft, prevent theft of valuables from a vehicle, deter vandalism, and to protect vehicle owners and occupants. A typical automobile security system, for example, includes a central processor or controller connected to a plurality of vehicle sensors. The sensors, for example, may detect opening of the trunk, hood, doors, windows, and also movement of the vehicle or within the vehicle. Ultrasonic and microwave motion detectors, vibration sensors, sound discriminators, differential pressure sensors, and switches may be used as sensors. In addition, radar sensors may be used to
10 monitor the area proximate the vehicle.

The controller typically operates to give an alarm indication in the event of triggering of a vehicle sensor. The alarm indication may typically be a flashing of the lights and/or the sounding of the

vehicle horn or a siren. In addition, the vehicle fuel supply and/or ignition power may be selectively disabled based upon an alarm condition. A typical security system also includes a receiver associated with the controller. The receiver cooperates with one or more remote transmitters typically carried by the user and which are used to arm and disarm the vehicle security system, for example. Other remote control features, such as locking or unlocking vehicle doors may also be performed.

The alarm indication provided at the vehicle is important to the overall effectiveness of the security system. For example, a weak alarm indication may do little to deter a would-be thief. A thief may also be more likely to target a vehicle when the vehicle is among hundreds of vehicles in a large parking lot, for example. In such a situation, the thief may be comforted in knowing that the alarm indication will not be identified by the vehicle's owner, since many audible alarm indications are generic.

Another disadvantage with many conventional security systems, especially minimal feature systems as typically installed by vehicle manufacturers, is that no shock sensing capability is provided. Accordingly, the alarm will only sound for opening of the vehicle doors, for example, and not when the vehicle is towed or lifted onto a truck and carried away. Since there is no shock sensor typically on such minimal feature security systems, there is no ability to provide a prewarn alarm that is less than the full alarm. The prewarn alarm in feature-rich aftermarket security systems may desirably warn off a would-be thief before serious damage is done to the vehicle. The prewarn, if falsely triggered, is also less intrusive than a full alarm.

[illegible][illegible][illegible][illegible]

OFF position and not operable responsive to the ignition being in the ON position.

The security controller is also typically switchable between an armed mode for causing the siren to generate the siren security alarm responsive to the at least one security sensor, and a disarmed mode. In addition, the vehicle security sensor may comprise a hood switch, and the shock detector may be operatively coupled to the security controller through the hood switch to simplify installation and connection of the siren. In other words, the siren shock sense output can be coupled to the hood switch, and the siren alarm will not sound unless the security controller is in the armed mode. This is so since the hood switch will not trigger an alarm unless the controller is in the armed mode.

Another aspect of the invention relates to the ability to provide a prewarn and full alarms. More particularly, the shock detecting circuit may generate a first output based upon detecting a shock within a first intensity range, and may generate a second output based upon detecting a shock within a second intensity range. The first intensity range may be less than the second intensity range, and the first output may then cause a reduced siren security alarm, or prewarn alarm, and the second output may cause the full siren security alarm.

In some embodiments, the commonly used E/M transducer may comprise a loudspeaker. In addition, the housing of the siren may be for mounting within a vehicle engine compartment.

Another aspect of the invention relates to a method for providing vehicle security. The method may comprise connecting a siren in the vehicle, the siren comprising a housing, a siren electrical signal

generator circuit carried by the housing, a shock detector circuit carried by the housing, and an electrical/mechanical (E/M) transducer carried by the housing. The method may also include generating an
5 electrical siren security alarm signal using the siren electrical signal generator circuit and sounding a siren security alarm responsive thereto using the E/M transducer. And the method may also include generating the electrical shock sense signal responsive to
10 mechanical shock using the E/M transducer and processing the electrical shock sense signal using the shock detector circuit.

Brief Description of the Drawings

15 FIG. 1 is a schematic block diagram of a vehicle security system including the siren in accordance with the present invention.

FIG. 2 is a more detailed schematic block diagram of the siren shown in FIG. 1.

20 FIG. 3 is a flowchart illustrating a first method embodiment in accordance with the invention.

FIG. 4 is a flowchart illustrating a second method embodiment in accordance with the invention.

FIG. 5 is a flowchart illustrating a third method
25 embodiment in accordance with the present invention.

Detailed Description of the Preferred Embodiments

1 5 The present invention will now be described more
fully hereinafter with reference to the accompanying
drawings, in which preferred embodiments of the
invention are shown. This invention may, however, be
embodied in many different forms and should not be
construed as limited to the embodiments set forth
herein. Rather, these embodiments are provided so that
this disclosure will be thorough and complete, and will
fully convey the scope of the invention to those
skilled in the art. Like numbers refer to like
elements throughout.

20 The vehicle security system **20**, including the
siren **50**, in accordance with the invention is first
described with reference to FIGS. 1 and 2. The
security system **20** includes a vehicle security
controller **22** which is illustratively positioned in the
vehicle passenger compartment **23** as is typical. The
security controller **22** is connected to one or more
vehicle security sensors, such as sensors 1-N, **24a-24c**,
respectively. As will be appreciated by those skilled
in the art, these sensors **24a-24c** may be various
switches or other sensors carried by the vehicle to
detect attempted theft or tampering with the vehicle.

25 A hood switch or position sensor **24d** is also
connected to the security controller **22** in the
illustrated embodiment. The hood switch **24d** is
typically positioned in the vehicle engine compartment
27 and detects opening of the vehicle hood as will also
30 be readily appreciated by those skilled in the art.
This hood switch **24d** may be advantageously used to
interface with the security controller **22** as will be
explained in greater detail below.

A receiver **31** and its associated antenna **33** may receive signals from a handheld remote transmitter **32**. For example, the remote transmitter **32** may include one or more buttons or switches **35a-35c** carried by a
5 housing **36**. These switches **35a-35c** may be used to arm or disarm the vehicle security controller **22**, or may be used to remotely open the vehicle trunk. The switches **35a-35c** may alternately or additionally be used to lock and unlock the vehicle doors remotely as will be
10 readily appreciated by those skilled in the art. The housing **36** may also carry a one or more keys, such as the ignition key **37**, as shown in the illustrated embodiment.

In some embodiments, the receiver **31** may be a
15 changing code receiver and the remote transmitter may be a changing code transmitter **32** for additional security. By changing code is meant that the remote transmitter **32** transmits at least a code portion which is pseudorandomly coded, and which is synchronized with
20 the receiver **31**. Accordingly, merely recording a transmission from the remote transmitter **32** and playing back the transmission with a so-called "code grabber" will not operate the changing code receiver **31** as will be appreciated by those skilled in the art.

25 The security controller **22** is also illustratively connected to an ignition switch **44**. In addition, the security controller **22** in the illustrated embodiment provides an alarm output via the vehicle horn **45**. More particularly, the horn **45** is electrically operable by
30 the user based upon the user selectively depressing a horn switch **43** which, in turn, selectively connects the horn to the vehicle power supply, such as the schematically illustrated vehicle battery **42**. In other

words, the horn switch **43** permits selective occasional operation of the horn **45** by the user, such as to signal other motorists or pedestrians when the user is operating the vehicle.

- 5 The vehicle security controller **22** is also
connected to drive or operate the horn **45**. For
example, and as will be readily appreciated by those
skilled in the art, the security controller **22** may be
connected to the horn **45** by splicing or connecting to
10 the appropriate wires as are accessible adjacent the
steering column within the passenger compartment **23**.
These wires pass through the firewall of the vehicle
into the engine compartment **27** as will be appreciated
by those skilled in the art.
- 15 The vehicle security controller **22** may operate the
horn **45** in a predetermined pattern to sound the horn
security alarm responsive to one or more of the
security sensors **24a-24d**, such as to indicate a vehicle
security breach. For example, the vehicle security
20 controller **22** may operate the horn **45** in a pattern
including a series of operations of the horn within a
predetermined time, and/or with each operation having a
predetermined duration. Alternately, the security
controller **22** may sound the horn **45** continuously for
25 longer than a predetermined time.

The security system 20 advantageously includes a siren 50 for sounding a siren security alarm to supplement a horn security alarm responsive to operation of the horn in the predetermined pattern, such as provided by the security controller 22. In addition, the siren 50 preferably does not sound the siren security alarm responsive to selective occasional operation of the horn 45, such as caused by the user pressing the horn switch 43.

For example, the horn operation detector circuit 53 may include a pattern detection circuit 61 (FIG. 2) which analyzes the driving signals to the horn 45 and determines whether, for example, X number of horn pulses are being provided within a give time T1, and/or whether a series of X horn pulses are being provided with each pulse having a length or duration of a predetermined time T2. The horn operation detector circuit 53 may also include a continuous pattern of operation detector circuit 62 which determines or detects whether the horn 45 is being operation for longer than a predetermined time T3. Of course, the outputs of these two pattern detector circuits 61, 62 can be combined with the illustrated OR gate 63, and, in turn, the output of the OR gate can be fed into an AND gate 64 which also receives the ignition OFF signal as an input.

The ignition OFF signal is illustratively provided via an inverting logic gate 65 connected to a switched positive voltage output of the ignition switch 44, so that when the ignition is OFF, a logic ONE is input to the input of the AND gate 64. Other logic circuitry and arrangements are contemplated by the present invention as will be appreciated by those skilled in the art.

The siren 50 by itself can be retrofitted to an existing vehicle security system 20 with only a few simple electrical connections readily made within the engine compartment 27. The complete security system 20 can also be readily and easily installed as a complete package as will also be appreciated by those skilled in the art.

In some embodiments, the siren 50 may be further enhanced to avoid false or undesired triggering of the

siren alarm, as when the horn 45 is manually operated by the user, by further basing sounding of the siren security alarm on the vehicle ignition switch 44 as mentioned briefly above. The vehicle typically includes the ignition switch 44 being switchable between ON and OFF positions. In accordance with this aspect of the invention, the siren 50 may sound the siren security alarm further responsive to detecting the ignition 44 being in the OFF position. In addition, the siren 50 may not sound the siren security alarm further responsive to detecting the ignition 44 being in the ON position. The horn 45 is typically manually operated by the user when driving with the ignition switch 44 in the ON position, avoiding sounding the siren security alarm with the ignition ON may also be desirable. This ignition sensing feature of the siren 50 may be used in combination with the horn operation pattern detecting, or may be used by itself.

To further aid the effective interfacing with the horn 45 and security controller 22, the siren 50 may have a start delay time so that sounding the siren security alarm is delayed after operation of the horn 45 is started. This may also reduce false or undesired triggering for manual operation of the horn 45. The siren 50 may also have a stop delay time so that sounding the siren security alarm continues only for a short time until after operation of the horn 45 is stopped. The start and/or stop delay may be implemented by the schematically illustrated start/stop delay(s) circuit 56 (FIG. 2) which may be a portion of the horn operation detector circuit 53. For example, the start delay may be 10 to 15 seconds, and, the stop

delay may be about 1 second. Other delays are also possible.

As shown in the illustrated embodiment, the siren 50 may comprise a housing 51, an audio alarm generator carried by the housing for sounding the siren security alarm, and a horn operation detector or detector circuit 53 carried by the housing for detecting operation of the horn 45, such as in the predetermined pattern and for operating the audio alarm generator responsive thereto. The horn operation detector circuit 53 may also detect the position of the ignition switch 44 as described above. The audio alarm generator may include the illustrated siren electrical signal generating circuit 54, and the E/M transducer 55, such as a loudspeaker, connected to the siren electrical signal generating circuit. In other terms, the audio alarm generator includes the circuitry 54 for generating the electrical siren drive signal, and the E/M transducer 55 for converting the electrical energy or signal into the mechanical or acoustical energy or audible signal.

The siren 50 may also include at least one energy storage device 58 (FIG. 2), such as a battery or capacitor to power the siren if power from the vehicle is not available. Typically, however, the energy storage device 58 may not be needed as the siren 50 can be powered from the vehicle battery 42 or electrical system, for example.

In one particularly, advantageous embodiment, the siren electrical signal generator circuit 54 may produce a multiple-tone siren pattern as disclosed in U.S. patent applications serial no. 09/374,178, filed August 13, 1999, and serial no. 09/596,547, filed June 19, 2000. The subject matter of each patent

application is incorporated herein by reference in its entirety.

- The E/M transducer 55 may be provided by a conventional loudspeaker, for example. The E/M
- 5 transducer 55 may include a metal frame 71 (FIG. 2) having a frusto-conical shape, and which mounts a high-powered permanent magnet 72 at its smaller end. A movable diaphragm 73 is also carried by the frame 71. The diaphragm 73 is connected to a voice coil 74
- 10 adjacent the permanent magnet 72. The voice coil 74, in cooperation with the permanent magnet 72, moves the diaphragm 73 responsive to the electrical drive signal from the siren electrical signal generator circuit 54. Movement of the diaphragm 73 generates the acoustic
- 15 waves or sounds for the siren security alarm indication. In other embodiments, the E/M transducer 55 may be based on piezoelectric or types of driving different than electromagnetic driving as will be appreciated by those skilled in the art.
- 20 In accordance with another advantageous feature of the invention, the siren 50 may include the illustrated shock detector circuit 80 connected to the E/M transducer 55 for determining a shock to the vehicle. The shock detector circuit 80 is also preferably
- 25 carried by the housing 51. The shock detector circuit 80 is for processing an electrical shock sense signal from the E/M transducer 55, and for generating a siren alarm indication and/or communicating the shock determination to the vehicle security controller 22.
- 30 The present invention takes advantage of the ability of the E/M transducer 55 to also convert mechanical or acoustic energy into electrical energy. As the diaphragm 73 is moved relative to the frame 71 by a

2025 RELEASE UNDER E.O. 14176

5 Patent No. 4,383,242 to Sassover et al. discloses, for example, using the stereo speakers of a vehicle entertainment system to detect unauthorized access attempts into the vehicle. The entire disclosure of this patent is incorporated herein by reference.

10 In accordance with this aspect of the invention,
the E/M transducer **55** and the associated circuitry
provide the dual alternate functions of sounding the
siren security alarm and sensing for shocks to the
vehicle. The siren **50** thus provides a compact,
15 portable, and readily installed device which can be
used alone or to upgrade an existing vehicle security
system, for example.

As described herein, the vehicle also typically includes an ignition switch **44** switchable between ON and OFF positions. To avoid undesired alarm soundings or shock sensing, such as when the user is entering or using the vehicle, the siren **50** may be operable as a shock sensor responsive to the ignition being in the OFF position and not operable responsive to the ignition being in the ON position.

Yet another feature of the invention also relates to avoiding false or undesired alarms. The vehicle security controller **22**, as described above, is also typically switchable between an armed mode and a disarmed mode, such as controlled by the remote transmitter **32**. In the armed mode, the security controller **22** causes the siren **50** and/or horn **45** to generate a security alarm responsive to the security sensors **24a-24d**. In the disarmed mode, the security

controller **22** does not generate such an alarm despite signals from the sensors **24a-24d** so that the user can use the vehicle. Accordingly, an output of the shock detector circuit **80** can be operatively coupled in
5 parallel with a nearby security sensor within the engine compartment **27**, such as the hood switch **24d**. Depending on the configuration of the hood switch **24d** circuit connection, the output of the shock detector circuit may be connected in electrical parallel or
10 series with the hood switch as will be appreciated by those skilled in the art.

When connected to the hood switch **24d**, and if the security controller **22** is armed, the output of the shock detector circuit **80** will cause the vehicle security
15 controller to be triggered, thereby causing generation of the horn and/or siren security alarms. Conversely, if the security controller **22** is in the disarmed mode, the output of the shock detector circuit **80** will not cause the security controller to generate an alarm.
20 Connection to the nearby sensor, such as the hood switch **24d**, greatly simplifies installation. Of course, other similar false or undesired alarm bypass techniques are also contemplated by the present invention, and, indeed other sensors could be connected to, in addition to, or
25 in place of the hood switch **24d**.

Another aspect of the invention relates to the ability of the siren **50** to provide a prewarn and full alarms in some embodiments. More particularly, the shock detecting circuit **80** may generate a first output
30 based upon detecting a shock within a first intensity range, and may generate a second output based upon detecting a shock within a second intensity range. The first intensity range may be less than the second intensity range, and the first output may then cause a

reduced siren security alarm, or prewarn alarm, and the second output may cause the full siren security alarm.

Referring more particularly to the more detailed schematic block diagram in FIG. 2 for the shock detector circuit 80, one approach to implement this dual shock detecting approach is now described in greater detail. The signal from the E/M transducer 55 is coupled through an amplifier 81 and filter 82 to a pair of comparators 83, 84. The prewarn alarm comparator 83 compares the input signal against a first threshold L1, and generates a prewarn output if the input signal is greater than L1. Similarly, the full alarm comparator 84 compares the input signal to a second higher threshold L2. If the input signal is above L2, then a full alarm output is generated by the full alarm comparator 84. Those of skill in the art will appreciate other equivalent signal detection circuits than can provide both a prewarn and full alarm output. In addition, more than two levels could also be provided. One or both of the comparators 83, 84 may also be provided with hysteresis, as will also be appreciated by those skilled in the art.

In the illustrated embodiment, the prewarn output from the prewarn alarm comparator 83 is connected to the siren electrical signal generator circuit 54. Accordingly, the siren 50 may generate a short chirp prewarn signal from the E/M transducer 55 after a prewarn level shock has been detected.

As also shown in the illustrated embodiment, the full alarm comparator 84 may have its output coupled to the hood switch 24d as described above to couple to the vehicle security controller 22. In yet other embodiments, both outputs could be coupled to the siren electrical signal generator 54 or both outputs could be

connected to the vehicle security controller 22 as will also be appreciated by those skilled in the art.

- Turning now additionally to the flowchart of FIG. 3 a method aspect of the invention is now described as
- 5 relates to a method for supplementing a horn security alarm in a vehicle. The vehicle is of a type including a horn 45 being electrically operable, a horn switch 43 permitting selective occasional operation of the horn by a user, at least one security sensor 24a-24d, and a
- 10 security controller 22 for operation of the horn to sound the horn security alarm responsive to the at least one security sensor. From the start (Block 100), the method may comprise monitoring the horn 45 for operation at Block 102, and sounding the siren security alarm
- 15 (Block 110) to supplement the horn security alarm responsive to detecting operation of the horn 45 in a predetermined pattern. The operation of the horn may be analyzed to determine whether an X number of pulses have been detected within time T1 at Block 104. If so, the
- 20 siren security alarm is sounded (Block 110). If not, the horn operation is analyzed to determine if each of X pulses has a time duration of T2 at Block 106. If so, the siren security alarm is sounded. If not, then at Block 108 it is determined whether the horn is being
- 25 continuously operated for longer than a time T3, and, if so, the siren security alarm is sounded. Accordingly, the siren security alarm is sounded when the horn 45 is operated in a predetermined pattern, such as would occur under control of the vehicle security controller 22, and
- 30 the siren security alarm is prevented from sounding responsive to selective occasional operation of the horn, such as by the user.

In one embodiment, analyzing or considering the horn pulses to determine the predetermined pattern may

2025 RELEASE UNDER E.O. 14176

comprise considering the number of leading and trailing edges of the power pulse used to sound the horn **45**. A single pressing of the horn switch **43** by the user will cause two edges within a predetermined time, such as
5 about 10 to 12 seconds. Accordingly, the method may prevent sounding the siren security alarm based upon detecting two transitions within this time. A vehicle security controller **22** may also provide a series of horn power pulses producing greater than nine transitions
10 within a set time, and this number is higher than a user would generate honking the horn several times within the predetermined time. In other terms, the number of transitions of the horn pulses can be counted, and if equal to one, or greater than nine, for example, the
15 siren security alarm is sounded, and otherwise the operation of the horn **45** is ignored.

As discussed above, sounding the siren security alarm at Block **110** can be delayed based upon a start-up delay time. In addition, while the siren security alarm
20 is being sounded, it may be desirable to continue to monitor the horn operation (Block **112**) to determine whether the horn has stopped at Block **114**. If not, the siren security alarm continues and the horn is also monitored until stoppage of the horn is detected at
25 Block **114**. The siren security alarm may be stopped at Block **116** before ending at Block **118**. Of course, a stop delay may also be provided before stopping sounding of the siren security alarm (Block **116**).

Another aspect of the invention relates to
30 monitoring the ignition **44** in addition to the horn **45**, as explained with reference to the flowchart of FIG. 4. From the start (Block **130**) both the horn **45** and the ignition switch **44** are monitored at Block **132** and Block **134**, respectively. If both the horn is being operated

2025 RELEASE UNDER E.O. 14176

(Block 136) and the ignition is OFF (Block 138) as determined at Block 140, the siren security alarm may be sounded at Block 142. Of course, the siren may be sounded after a start delay if desired.

- 5 The siren will continue to sound until monitoring the horn (Block 144) indicates that the horn has stopped (Block 146). The siren security alarm may then be stopped at Block 148 before ending (Block 150). The stop delay may also be provided. In this illustrated
- 10 embodiment, the sounding of the siren security alarm is based upon both the ignition switch 44 being OFF and the horn 45 being operated. The concept of determining that the horn 45 is being operated in a predetermined pattern can also be combined with the ignition monitoring in
- 15 accordance with the invention as will be understood by those skilled in the art.

- Turning now additionally to the flowchart of FIG. 5, the shock sensing feature of the present invention will be further described. From the start (Block 160),
- 20 the E/M transducer 55 may be monitored for operation by the siren electrical signal generator circuit 54 (Block 132), and while the ignition switch 44 is also monitored (Block 164). If the E/M transducer 55 is sounding, the shock sensing feature is, of course, bypassed (Block
- 25 166). Also, in the illustrated embodiment, if the ignition switch is ON (Block 168), the shock sensing feature is also bypassed. If, however, the E/M transducer 55 is idle, and the ignition switch 44 is OFF as determined at Block 170, then the E/M transducer is
- 30 monitored at Block 172 for shock signals.

 If the shock signal is greater than a first threshold or value L1 (Block 174), a prewarn output may be given at Block 176. If the shock signal is also

greater than a second threshold or value L2 (Block 178), the a full siren security alarm output may be given at Block 180, before stopping at Block 182. Both outputs could be given for the higher threshold shock or the
5 prewarn output could be suppressed. In addition, the prewarn and full alarm output signals could be multiplexed for communication over a single pair of wires to the vehicle security controller 22 as will be readily appreciated by those skilled in the art. Other
10 details and aspects of this method of the invention are described in greater detail above, and require no further description at this time.

Considered in somewhat different terms, this method aspect may include connecting a siren 50 in the vehicle,
15 the siren comprising a housing 51, a siren security alarm generator circuit 54 carried by the housing, a shock detector circuit 80 carried by the housing, and an E/M transducer 55 carried by the housing. The method may also include generating an electrical siren security
20 alarm signal using the siren security alarm generator 54 and sounding a siren security alarm responsive thereto using the E/M transducer 55. The method may also include generating the electrical shock sense signal responsive to mechanical shock using the E/M transducer
25 55 and processing the electrical shock sense signal using the shock detector circuit 80.

Many modifications and other embodiments of the invention will come to the mind of one skilled in the art having the benefit of the teachings presented in the
30 foregoing descriptions and the associated drawings. Therefore, it is to be understood that the invention is not to be limited to the specific embodiments disclosed, and that other modifications and embodiments are

intended to be included within the scope of the appended claims.

09650425.082900

THAT WHICH IS CLAIMED IS:

1. A vehicle security system comprising:
at least one security sensor and a security
controller connected thereto;

a siren comprising

5

a housing,

a siren electrical signal generator circuit carried by said housing for generating an electrical siren security alarm signal responsive to said security controller,

10

a shock detector circuit carried by said housing for processing an electrical shock sense signal for said security controller, and

an electrical/mechanical (E/M) transducer carried by said housing for sounding a siren security alarm responsive to the electrical siren security alarm signal, and for generating the electrical shock sense signal responsive to mechanical shock.

15

2. A vehicle security system according to Claim 1 wherein the vehicle includes an ignition switchable between ON and OFF positions; and wherein said siren is operable responsive to the ignition being in the OFF position and is not operable responsive to the ignition being in the ON position.

3. A vehicle security system according to Claim 1 wherein said security controller is switchable between an armed mode for causing said siren to generate the siren security alarm responsive to said at least one security sensor, and a disarmed mode.

5

4. A vehicle security system according to Claim 3 wherein said at least one vehicle security sensor comprises a hood switch; and wherein said shock detector is operatively coupled to said security controller
5 through said hood switch.

5. A vehicle security device according to Claim 1 wherein said shock detecting circuit generates a first output based upon detecting a shock within a first intensity range, and generates a second output based
5 upon detecting a shock within a second intensity range.

6. A vehicle security device according to Claim 5 wherein the first intensity range is less than the second intensity range; and wherein the first output causes a reduced siren security alarm and the second
5 output causes a full siren security alarm.

7. A vehicle security device according to Claim 1 wherein said E/M transducer comprises a loudspeaker.

8. A vehicle security system according to Claim 1 wherein said housing is for mounting within a vehicle engine compartment.

9. A vehicle security system according to Claim 1 further comprising a receiver connected to said security controller, and at least one remote transmitter communicating with said receiver.

10. A vehicle security system according to Claim 9 wherein said receiver and said at least one remote transmitter operate with changing codes.

2025 RELEASE UNDER E.O. 14176

11. A siren for operation with a vehicle security system comprising at least one security sensor and a security controller connected thereto, the siren comprising:

- 5 a housing;
- a siren electrical signal generator circuit carried by said housing for generating an electrical siren security alarm signal responsive to the security controller;
- 10 a shock detector circuit carried by said housing for processing an electrical shock sense signal for the security controller; and
- an electrical/mechanical (E/M) transducer carried by said housing for sounding a siren security alarm
- 15 responsive to the electrical siren security alarm signal, and for generating the electrical shock sense signal responsive to mechanical shock.

12. A siren according to Claim 11 wherein the vehicle includes an ignition switchable between ON and OFF positions; and wherein said siren is operable responsive to the ignition being in the OFF position and
- 5 is not operable responsive to the ignition being in the ON position.

13. A siren according to Claim 11 wherein the security controller is switchable between an armed mode for causing said siren to generate the siren security alarm responsive to said at least one security sensor,
- 5 and a disarmed mode.

14. A siren according to Claim 13 wherein the at least one vehicle security sensor comprises a hood switch; and wherein said shock detector is operatively

2025 RELEASE UNDER E.O. 14176

coupled to the security controller through the hood
5 switch.

15. A siren according to Claim 11 wherein said
shock detecting circuit generates a first output based
upon detecting a shock within a first intensity range,
and generates a second output based upon detecting a
5 shock within a second intensity range.

16. A siren according to Claim 15 wherein the
first intensity range is less than the second intensity
range; and wherein the first output causes a reduced
siren security alarm and the second output causes a full
5 siren security alarm.

17. A siren according to Claim 11 wherein said E/M
transducer comprises a loudspeaker.

18. A siren according to Claim 11 wherein said
housing is for mounting within a vehicle engine
compartment.

19. A siren comprising:
a housing;
a siren electrical signal generator circuit carried
by said housing for generating an electrical siren
5 security alarm signal;
a shock detector circuit carried by said housing
for processing an electrical shock sense signal; and
an electrical/mechanical (E/M) transducer carried
by said housing for sounding a siren security alarm
10 responsive to the electrical siren security alarm
signal, and for generating the electrical shock sense
signal responsive to mechanical shock.

20. A siren according to Claim 19 wherein the vehicle includes an ignition switchable between ON and OFF positions; and wherein said siren is operable responsive to the ignition being in the OFF position and is not operable responsive to the ignition being in the ON position.

21. A siren according to Claim 19 wherein said shock detecting circuit generates a first output based upon detecting a shock within a first intensity range, and generates a second output based upon detecting a shock within a second intensity range.

22. A siren according to Claim 21 wherein the first intensity range is less than the second intensity range; and wherein the first output causes a reduced siren security alarm and the second output causes a full siren security alarm.

23. A siren according to Claim 19 wherein said E/M transducer comprises a loudspeaker.

24. A siren according to Claim 19 wherein said housing is for mounting within a vehicle engine compartment.

25. A method for providing vehicle security comprising:

connecting a siren in the vehicle, the siren comprising a housing, a siren electrical signal generator circuit carried by the housing, a shock detector circuit carried by the housing, and an electrical/mechanical (E/M) transducer carried by the housing;

- generating an electrical siren security alarm
- 10 signal using the siren electrical signal generator circuit and sounding a siren security alarm responsive thereto using the E/M transducer; and
- generating the electrical shock sense signal responsive to mechanical shock using the E/M transducer
- 15 and processing the electrical shock sense signal using the shock detector circuit.

26. A method according to Claim 25 wherein the vehicle includes an ignition switchable between ON and OFF positions; and further comprising operating the siren responsive to the ignition being in the OFF
- 5 position and not operating the siren responsive to the ignition being in the ON position.

27. A method according to Claim 25 further comprising using the shock detecting circuit to generate a first output based detecting a shock within a first intensity range, and to generate a second output based
- 5 upon detecting a shock within a second intensity range.

28. A method according to Claim 27 wherein the first intensity range is less than the second intensity range; and further comprising generating a reduced siren security alarm responsive to the first output, and
- 5 generating a full siren security alarm responsive to the second output.

29. A method according to Claim 25 wherein the E/M transducer comprises a loudspeaker.

30. A method according to Claim 25 wherein connecting the siren in the vehicle comprises

positioning the housing within a vehicle engine compartment.

2023

VEHICLE SECURITY SYSTEM SHOCK SENSING SIREN AND ASSOCIATED METHODS

Abstract of the Disclosure

A vehicle security system may include at least one security sensor and a security controller connected thereto, and a siren which also serves as a shock sensor. The siren may include a housing, a siren security electrical signal generator circuit carried by the housing for generating an electrical siren security alarm signal responsive to the security controller, and a shock detector circuit carried by the housing for processing an electrical shock sense signal for the security controller. The siren also preferably includes an electrical/mechanical (E/M) transducer carried by the housing for sounding a siren security alarm responsive to the electrical siren security alarm signal, and for generating the electrical shock sense signal responsive to mechanical shock. In other words, the E/M transducer and associated circuitry provide the dual alternate functions of sounding the siren security alarm and sensing for shocks to the vehicle.




FIG. 1




Fig. 2

09650425-082900




Fig. 3




Fig. 4




Fig. 5

DECLARATION AND POWER OF ATTORNEY FOR PATENT
APPLICATION

Attorney Docket No.: 58072

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: **VEHICLE SECURITY SYSTEM SHOCK SENSING SIREN AND ASSOCIATED METHODS**, the specification of which:

(check one)

 X is attached hereto

 was filed on

as Application Serial No.

and was amended on
(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulation, 1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the of the application on which priority is claimed:

Prior Foreign Application(s) Priority Claimed

(Number)	(Country)	(Day/Month/Year Filed)	[] Yes	[] No
(Number)	(Country)	(Day/Month/Year Filed)	[] Yes	[] No
(Number)	(Country)	(Day/Month/Year Filed)	[] Yes	[] No

I hereby claim the benefit under Title 35, United States Code, 120, of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Appln Serial No.) (patented, pending, aban.)	(Filing Date)	(Status)
(Appln Serial No.) (patented, pending, aban.)	(Filing Date)	(Status)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

English Language Declaration

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorneys to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: Christopher F. Regan, Reg. No. 34,906; Herbert L. Allen, Reg. No. 25,322; David L. Sigalow, Reg. No. 36,006; Jeffrey S. Whittle, Reg. No. 36,382; Richard K. Warther, Reg. No. 32,180; Michael W. Taylor, Reg. No. 43,182; Henry Estevez, Reg. No. 37,823; Paul J. Ditzner, Reg. No. 40,455; John F. Woodson, II, Reg. No. 45,236; and Charles E. Wands, Reg. No. 25,649; Carl M. Napolitano, Reg. No. 37,405; Jacqueline E. Bartt, Reg. No. 37,845; Mark B. Malek, Reg. No. P-46,894.


Send Correspondence to:

CHRISTOPHER F. REGAN, ESQUIRE
ALLEN, DYER, DOFFELT, MILBRATH & GILCHRIST, P.A.
P.O. Box 3791
Orlando, Florida 32802-3791

Direct Telephone Calls to:

Christopher F. Regan
(407) 841-2330

Full name of (first) inventor: **KENNETH E. FLICK**

Inventor's
Signature: 

Date: 8-29-07

Residence: **Douglasville, Georgia 30135**

Citizenship: **Citizen of the United States of America**

Post Office Address: **5236 Presley Place
Douglasville, GA 30135**